

Cost-effective and Secure Ringlock Scaffolding System with Safety Factor ≥4

Basic Information

Place of Origin: ChinaBrand Name: BythaiModel Number: BT03



Product Specification

• Standard: EN12810 & EN12811

Max Height: ≤30mHorizontal Adjustment: ≤±3°

Components: Vertical, Horizontal, Diagonal, Brace, Base

Plate, Ladder, Etc.

Joints: Double-lockingWeight: ≤30kg/m2

Safety Factor: ≥4

• Vertical Load Capacity: ≥45KN

Product Description:

Ringlock System Scaffolding is a type of formwork scaffolding product that is mainly constructed with ringlock ledger, which provides the highest safety factor of \geq 4, and is hot-dip galvanized for better surface treatment. With Horizontal Load Capacity of \geq 15KN and weight of \leq 30kg/m2, it is a lightweight and stable solution, and the Vertical Adjustment of \leq ±3° allows for easy adjustment and installation. This Ringlock System Scaffolding is ideal for formwork and other applications, and is highly recommended for anyone looking for a reliable Ringlock formwork solution.

Technical Parameters:

Attribute	Value
Safety Factor	>=4
Surface Treatment	Hot-dip Galvanized
Size	48.3mm
Vertical Adjustment	<=±3°
Joints	Double-locking
Weight	<=30kg/m2
Max Height	<=30m
Material	Q235 Steel
Horizontal Load Capacity	>=15KN
Warranty	2 Years

Applications:

Bythai BT03 Ringlock System Scaffolding is an ideal scaffolding system for a wide variety of applications. It is made of Q235 Steel and has a Hot-dip Galvanized surface treatment for superior durability and strength. The Ringlock System Scaffolding allows for a Horizontal Adjustment of up to ±3°, and has a Vertical Load Capacity of ≥45KN and a Horizontal Load Capacity of ≥15KN. It is perfect for Ringlock accessories, Scaffolding Ringlock, Ringlock formwork, Steel frame scaffolding, Structural Scaffolding and other Scaffolding System applications.

Customization:

Customized Ringlock System Scaffolding from Bythai(BT03)

Brand Name: Bythai Model Number: BT03 Place of Origin: China Weight: ≤30kg/m2 Size: 48.3mm Safety Factor: ≥4

Surface Treatment: Hot-dip Galvanized Vertical Load Capacity: ≥45KN

Bythai's BT03 Ringlock System Scaffolding is specifically designed to provide the highest safety factor and vertical load capacity for your construction projects. It is made with hot-dip galvanized surface treatment which gives it superior strength and durability, and its lightweight design ensures easy installation and transport. The BT03 Ringlock System Scaffolding ensures a safety factor of \geq 4, a weight of \leq 30kg/m2, a size of 48.3mm, and a vertical load capacity of \leq 45KN.

Packing and Shipping:

Ringlock System Scaffolding Packaging and Shipping

The Ringlock System Scaffolding is packaged and shipped as follows:

All parts and components are packaged in individual boxes.

The boxes are then secured in a wooden crate, which is then shrink-wrapped.

The boxes are then shipped via ground transportation.

FAQ:

Q: What is the brand name of Ringlock System Scaffolding?

A: The brand name of Ringlock System Scaffolding is Bythai.

- Q: What is the model number of Ringlock System Scaffolding?
- A: The model number of Ringlock System Scaffolding is BT03.
- Q: Where is Ringlock System Scaffolding produced?
- A: Ringlock System Scaffolding is produced in China.
- Q: What is the material of Ringlock System Scaffolding?
- A: Ringlock System Scaffolding is made of high strength steel.
- Q: What is the size of Ringlock System Scaffolding?
- A: Ringlock System Scaffolding is available in three sizes: 1.37m, 1.80m and 2.44m.



Bythai Scaffolding Co.,Ltd



17300780862



info@bythaiscaffolding.com



bythaiscaffold.com

No. 605, Industrail Exchange Center, Huanghua Town Changsha Hunan China